

PROFESSIONAL AUDIO SYSTEMS

AUDIO SOUND SOURCES

2VSPRS	Double-deck audio player, FM tuner with 60 presets and RDS function, CD/USB/SD card readers, IR remote control, priority output, Vari-Speed digital control for track tempo's modification, RS-232 control interface	€ 495,00
---------------	--	----------

P.A. INSTALLATION MIXERS

SAM312	P.A. Installation Mixer. Rotary faders, 3 channels, 6 inputs, phantom for mic inputs, 2 outputs, remote mute interconnection for fire alarm, one rack unit height.	€ 343,00
SAM412T	1 U rack installation mixer. 4 MIC/LINE inputs. Tone controls in each input. MIX input. OUT and REC outputs. <i>Talkover</i> function in input #1. General remote MUTE.	€ 483,00
SAM512T	P.A. Installation Mixer. Rotary faders, 5 channels, 10 inputs, phantom for mic inputs, 2 independent outputs, remote mute interconnection for fire alarm, adjustable talkover, one rack unit height.	€ 565,00
SAM614T	P.A. Installation Mixer. Rotary faders, 6 channels, 12 inputs, phantom for mic inputs, balanced independent outputs, routing from any input to any output, one unit rack height	€ 761,00
COMPACT5	Universal mixer, versatile lap top and rack format design (3u. high / 19" rack), 8 LINE inputs, 3 MICRO inputs, 2 PHONO inputs, 5 channels with 45 mm. sliders, 3 band eq. per channel, talkover, 2 independent outputs (main balanced)	€ 595,00
COMPACT8	Universal mixer, versatile lap top and rack format design (4u. high / 19" rack), 8 channels with COMBO connectors, 8 MICRO inputs, 7 LINE inputs (High/Low) plus AUX on front panel, 3 PHONO inputs, 8 channels with 60 mm. sliders, 3 band eq. per channel including semi-parametric mid freq adjustments for accurate MIC input eq, talkover, 2 independent outputs (main balanced) plus REC output. Phantom.	€ 1.078,00
MPAGE1	1-zone paging station compatible with any device including a phantom-powered microphone input (pKUB, SAM series, COMPACT series, AMI2-70, MIMO54, MIMO88, etc.). PAGE control output for third-party remote control. Gooseneck microphone included.	€ 161,00

ZONERS

DAM514	Digital audio mixer including 5 audio inputs (3 stereo LINE + 2 MIC/LINE inputs) and 4 audio outputs (mono or stereo-paired), DSP processing @ 24 bits / 48kHz, RS-232 connectivity and 4 REMOTE control ports (0-10VDC, WPm series compatible). Front panel LCD display, 2x20 characters. Front panel configuration keys + digital encoder. PAGER and MUTE control ports. EclerCOMM software (free) and CA-NET protocol compatible. 1 RU format.	€ 766,00
MIMO54	4 ST input sources / 4 MONO zone outputs analog matrix + additional 5th input for direct interfacing with priority and/or evacuation messages. Dedicated 2 band tone control for each zone output. Optional remote wall panels for source selection and/or volume control available. Security caps for front knobs substitution included. 1 RU height.	€ 807,00



MIMO88	8 IN / 8 OUT digital audio matrix, fully programable and linkable to a second unit (16x16), real routing from any input to any output, management via Ethernet with EclerNet Manager, TP-NET third party control protocol for integration to CRESTRON, AMX, EXTRON, 8 GPI ports, 8 GPO ports, DSP processing, virtual and physical paging station management, schedule events. It includes RS-232 connection for third party devices	€ 1.995,00
MPAGE1	1-zone paging station compatible with any device including a phantom-powered microphone input (pKUB, SAM series, COMPACT series, AMI2-70, MIMO54, MIMO88, etc.). PAGE control output for third-party remote control. Gooseneck microphone included.	€ 161,00
MPAGE4	4-zone paging station for the recently upgraded MIMO54, that now allows for real-time paging. 4 zone selection + ALL & PAGE keys. Selectable chime melody and gooseneck microphone	€ 258,00
MPAGE16	Digital paging console for MIMO 88, 16 zones, SELECT ALL, CLEAR and PAGING keys, two user-define function keys (ie: for presets)	€ 516,00
WPMVOLSR	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (source selection and zone volume). RJ45 standard connector. Volume control compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 80,00
WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00
WPTOUCH	Touch-sensitive wall panel remote control with LCD transfective display. Digital remote control, compatible with the incoming MIMO88 digital matrix (CAN-BUS). 2 touch-sensitive keys. 1 touch-sensitive jog wheel. 1 IR receiver. 2x16 char. LCD transfective display. Programmable under the incoming MIMO88 control (digital mode). Compatible with the MIMO54 for both volume control and source selection (analogue mode). Compatible with other products with 0-10 VDC ports (MPA, AMIC, AMPACK, etc.) for volume control (using an external power supply). Recessed or top-wall mount with included accessory.	€ 269,00
NEW WPMSCREEN	EclerNet touch-screen wall panel. The WPMSCREEN is a remote control panel compatible with all the EclerNet products, like MIMO88, NXA series and NPA series. It features a 7" touchscreen, RJ45 Ethernet interface and an integrated UCP (User Control Panel) client and server hardware: no computer is required to become a UCP webserver, once one or more WPMSCREEN units are installed in an EclerNet project. Each unit can be configured by means of the UCP control system as a local zone control or as a global installation control, being able to work simultaneously with other WPMSCREEN units and/or also with third-party UCP clients (iOS®, Android®, Windows®, etc.). The WPMSCREEN includes a power supply unit and surface mount installation box. It is as well compatible with standard recessed boxes and the standard VESA75 mount system.	€ 715,00



MIXER-AMPLIFIERS

	CA40	2 x 20 W RMS @ 4 Ω mixer-amplifier in compact format with light and silent (fanless) design; 1 balanced MIC input with phantom power and high-class preamp including noise gate and talkover function over the rest of inputs; 2 unbalanced LINE inputs; 2-band tone control (Bass, Treble) independent for the MIC and LINE buses; AUX output for external link to other devices or amplifiers; AUTO STANDBY function; STEREO, PARALLEL and BRIDGE modes; digital local control encoder type; infrared remote control included; remote control compatible with WPmVOL and WPmVOL-SR wall panels (0-10 VDC); RS-232 control port compatible with CA-NET protocol; MUTE port for external muting of the unit when an evacuation system must be activated; external, universal and CE/UL/CCC certified power supply	€ 239,00
NEW	CA120	2 x 60 W RMS @ 4 ohms mixer-amplifier in compact format with light and silent (fanless) design. 1 MIC (balanced) / LINE input with phantom power and high-class preamp including noise gate and talkover function over the rest of inputs. 2 unbalanced LINE inputs. 2-band tone control (Bass, Treble) independent for the MIC/L3 and L1/L2 buses. AUX output for external link to other devices or amplifiers. AUTO STANDBY function. STEREO and PARALLEL(mono) modes. Digital local control encoder type. Infrared remote control included. Remote control compatible with WPmVOL and WPmVOL-SR wall panels (0-10 VDC). RS-232 control port compatible with CA-NET protocol and EclerCOMM software app. MUTE port for external muting of the unit when an evacuation system must be activated. External, universal and CE/UL/CCC certified power supply	€ 349,00
NEW (May 2015)	CA120HZ	1 x 120 W RMS @ 70/100V line level. Mixer-amplifier in compact format with light and silent (fanless) design. 1 balanced MIC / unbalanced LINE input with phantom power and high-class preamp including noise gate and talkover function over the rest of inputs. 2 unbalanced LINE inputs. 2-band tone control (Bass, Treble) independent for the MIC/LINE and the LINE buses. AUX output for external link to other devices or amplifiers. AUTO STANDBY function. Digital local control encoder type. Infrared remote control included. Remote analogue control compatible with WPmVOL and WPmVOL-SR wall panels (0-10 VDC). RS-232 control port compatible with CA-NET protocol. MUTE port for external muting of the unit when an evacuation system must be activated. External, universal and CE/UL/CCC certified power supply	NNB
	CA200Z	Digital mixing amplifier with 6 audio inputs and 2 independent output zones (2 x 70 Wrms). STEREO, MONO, BRIDGE and ZONES A/B operating modes. 4 LINE ins. 2 MIC ins with talkover/pager function and 2-level priority system. Pager input for an MPAGE4 paging station. 2 REMOTE control ports for volume Control and source/preset selection, compatible with WPm wall panels. RS-232 interface. IR remote control included. MUTE port. 5 preset memories. 1/2 RU width	€ 493,00
	2UHRMKIT	Rack mount kit for the CA200Z and HMA120. It lets its installation in half-width rack frames, as well as in 19" standard (full width) frames	€ 52,00
	TR270	Dual transformer unit to convert CA200Z into 100 V line. It can be racked with C2UHRMKIT	€ 115,00
	HMA120	Self-powered Media mixer. Self-powered mixer including an integrated media player and 5 external audio inputs: 3 x LINE ST, 1 MIC/LINE and 1 MIC. Class D, 120W powered output that supports both low (4 Ω) and high (70V, 100V) impedance loudspeaker lines. Convection cooling (100% silent). 2 level priority system (paging, emergencies, etc.). Auto stand-by mode. AUX OUT and additional remote control port (source selection and output volume) compatible with WPm series wall panels.	€ 375,00



HMA180	Self-powered installation Public Address mixer. 4 MIC balanced inputs with bus phantom power (selectable); 4 LINE inputs, independent 3 band EQ for MIC inputs and LINE inputs; pager & chime function MIC1 input (voice level or contact closure activation); additional EMERGENCY MIC/LINE input; remote volume control port (0 – 10 VDC); remote MUTE control port; 24 VDC control output linkable to the PAGER and/or EMERGENCY functions (to activate the priority relays in remote volume controls); subsonic filter (@ 70 Hz); insertion point in TRS format; 8Ω , 70 V, 100 V powered output with class D 180 W amplifier, convection cooled (100% silent); LINE level AUX output and internal & universal power Supply	€ 495,00
MPAGE1	1-zone paging station compatible with any device including a phantom-powered microphone input (pKUB, SAM series, COMPACT series, AMI2-70, MIMO54, MIMO88, etc.). PAGE control output for third-party remote control. Gooseneck microphone included.	€ 161,00
WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00
DIGITAL PROCESSORS		
AMIC24	19" 1 unit rack DSP including AMIC Lab software. 2 inputs and 4 outputs, 24 bits-48 KHz, Level, mute and remote control adjust. Phase inverter. Delay. Crossover type and slope adjustable. 10 parametric equalizers per channel. Test signal generator. Password locking option. Graphical screen.	€ 749,00
NEW (March 2015) ALMA24	19" 1 unit rack DSP including EclerCOMM software. 2 inputs and 4 outputs, 24 bits-48 KHz, Level, mute and remote control adjust. Phase inversion. Delay time, LP and HP crossovers and 8 parametric EQ filters per each input and each output. Compressors/limiter for inputs and double compressor/limiter (one peak, one RMS) for outputs. Test signal generator. Password locking option. Configuration templates and user presets.	€ 749,00
WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00
ALMA26	Digital loudspeaker manager including 2 audio inputs and 6 audio outputs electronically balanced, 24 bits-48 KHz , USB interface and 2 volume remote control ports (0-10VDC), full DSP, labels edition, password protected, system templates, 20 presets. Fully configurable from PC via ECLERCOMM control software	€ 799,00



100 V LINE AMPLIFIERS

HZA470F	Four MERGING channels amplifier with direct 100 V line (high impedance) output. SPM 100 Technology - Channel N which allows 100 V speaker lines connection without using output transformers: excellent audio quality (specially in the low-end frequencies) and convection cooling 100% silent. 4 mono balanced inputs, 4 x 70W outputs, 4 volume remote control ports (10 V DC), autostandby, thermal and overload protections, anti-clip system. Every 2 adjacent channels can be merged, getting one out of these possible configurations: -4 x 70W @ 100 V line outputs -2 x 70W + 1 x 140 W @ 100 V line outputs -2 x 140W @ 100 V line outputs -1 x 70W + 1 x 210 W @ 100 V line outputs -1 x 280W @ 100 V line output	€ 830,00
HZA4120F	Four MERGING channels amplifier with direct 100 V line (high impedance) output. SPM 100 Technology - Channel N which allows 100 V speaker lines connection without using output transformers: excellent audio quality (specially in the low-end frequencies) and convection cooling 100% silent. 4 mono balanced inputs, 4 x 120W outputs, 4 volume remote control ports (10 V DC), autostandby, thermal and overload protections, anti-clip system. Every 2 adjacent channels can be merged, getting one out of these possible configurations: -4 x 120W @ 100 V line outputs -2 x 120W + 1 x 240 W @ 100 V line outputs -2 x 240W @ 100 V line outputs -1 x 120W + 1 x 360 W @ 100 V line outputs -1 x 480W @ 100 V line output	€ 1.039,00
WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00
HSA300	Single channel, 300 W amplifier with direct 100 V line (high impedance). SPM 100 Technology - Channel N which allows 100 V speaker lines connection without using output transformers, thus delivering excellent audio quality (specially in the low-end frequencies). Thermal and overload protections. Anti-clip system.	€ 547,00
NEW (Feb. 2015) HSA2400	Stereo, 2x 400 W RMS @ 4 Ω and 70/100 V line level, high efficiency amplifier. Auto stand-by function and fanless design, 100% silent. REMOTE ports (0-10VDC) compatible with WPM series wall panels. Switchable HP filter. Thermal and overload protections. Anti-clip system.	NNB

COMPACT AMPLIFIERS

AMPACK270	Ultra light weight compact amplifier, 2x70 W RMS @ 4 ohm. Fanless ventilation (100% silent), VCA ports (volume remote control). STEREO, PARALLEL an BRIDGE operation modes. Auto Stand By. DIN rail mount ready.	€ 496,00
AMPACK470	Ultra light weight compact amplifier, 4x70 W RMS @ 4 ohm. Fanless ventilation (100% silent), VCA ports (volume remote control). INDEPENDENT, PARALLEL an BRIDGE operation modes. Auto Stand By. DIN rail mount ready.	€ 616,00
DLAPACK270	Ampack's powered output transformer unit: low impedance to 100 V line level, 2 channels. DIN rail mount ready.	€ 258,00
WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00



MULTICHANNEL AMPLIFIERS		
MPA480R	Four channels power amplifier, 78 W/channel into 4 ohms, remote control per channel, stack output, 5 different ways of performance, noiseless technology, 2 u. Rack ☐ 2 Stereo channels + 1 bridged channel full range ☐ 2 Bridged channels ☐ 4 Channels quadraphonic ☐ 4 Channels stereo ☐ 4 Channels mono	€ 695,00
MPA680R	Six channels power amplifier, 78 W/channel into 4 ohms, remote control per channel, stack output, 5 different ways of performance, noiseless technology, 2 u. Rack ☐ 4 Stereo channels + 1 bridged channel full range ☐ 3 Bridged channels ☐ 6 Channels quadraphonic ☐ 6 Channels stereo ☐ 6 Channels mono	€ 895,00
MPA4150R	Four channels power amplifier, 4 x 150 W @ 4 ohms, remote control per channel, stack output, 6 different ways of performance, Class D technology, fanless design, 100% silent. 2 u. Rack ☐ 2 Stereo channels + 1 bridged channel for subwoofer ☐ 2 Stereo channels + 1 bridged channel full range ☐ 2 Bridged channels ☐ 4 Channels quadraphonic ☐ 4 Channels stereo ☐ 4 Channels mono	€ 995,00
MPA6150R	Six channels power amplifier, 6 x 150 W @ 4 ohms, remote control per channel, stack output, 6 different ways of performance, Class D technology, fanless design, 100% silent. 2 u. Rack ☐ 4 Stereo channels + 1 bridged channel for subwoofer ☐ 4 Stereo channels + 1 bridged channel full range ☐ 3 Bridged channels ☐ 6 Channels quadraphonic ☐ 6 Channels stereo ☐ 6 Channels mono	€ 1.349,00
MPA4400R	Four channels power amplifier, 410 W/channel into 4 ohms, remote control per channel. stack output. 6 different ways of performance. SPM technology. 2 u. Rack ☐ 2 Stereo channels + 1 bridged channel for subwoofer ☐ 2 Stereo channels + 1 bridged channel full range ☐ 2 Bridged channels ☐ 4 Channels quadraphonic ☐ 4 Channels stereo ☐ 4 Channels mono	€ 1.534,00
WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00



ENTRY LEVEL ANALOGUE STEREO POWER AMPLIFIERS

INSTALLATION	Light weight stereo amplifier, affordable for every budget. Multiple types of inputs and outputs. The integrated crossover function, when activated, sends the low frequency band to channel 1 and the high frequency band to channel 2 (cross point at 150 Hz), making easy and quick to set up a two-way channel configuration without the need of external processing.		
LPA6000	Power Unit 320 W/channel into 4 ohms, 210 W/channel into 8 ohms, 5 Kg.	€	445,00
LPA10000	Power Unit 500 W/channel into 4 ohms, 330 W/channel into 8 ohms, 7 Kg.	€	495,00
LPA16000	Power Unit 760 W/channel into 4 ohms, 450 W/channel into 8 ohms, 9 Kg.	€	682,00

ANALOGUE STEREO POWER AMPLIFIERS

High Efficiency Mosfet amplifiers. Input gain control on the front panel with locking system. Fully protected (clip, thermal and front panel indicators). Progressive forced ventilation, temperature controlled. Built-in anticlip circuit. Switchable subsonic filter. Selector Stereo-Bridge-Parallel. Input sensitivity selector. Balanced inputs on XLR3 connectors. Speak on outputs. Two units rack.

XPA3000	Power Unit 295 W/channel into 4 ohms, 198 W/channel into 8 ohms, 17 Kg.	€	641,00
XPA5000	Power Unit 498 W/channel into 4 ohms, 314 W/channel into 8 ohms, 19,7 Kg.	€	769,00
XPA7000	Power Unit 718 W/channel into 4 ohms, 450 W/channel into 8 ohms, 21,9 Kg.	€	988,00
XPA11000	Power unit 1180 W RMS/4ohms. 745 W RMS/8ohms. 2 RU. 22,6 Kg	€	1.251,00

HIGH EFFICIENCY POWER AMPLIFIERS

NEW <i>(Jan. 2015)</i>	GPA2400	Stereo, 2x 360 W RMS @ 4 Ω, high efficiency amplifier (class D). Auto stand-by function and fanless design, 100% silent. REMOTE ports (0-10VDC) compatible with WPM series wall panels. Switchable HP filter. Thermal and overload protections. Anti-clip system.	NNB
NEW <i>(March 2015)</i>	GPA2800	Stereo, 2x 720 W RMS @ 4 Ω, high efficiency amplifier (class D). Auto stand-by function and fanless design, 100% silent. REMOTE ports (0-10VDC) compatible with WPM series wall panels. Switchable HP filter. Thermal and overload protections. Anti-clip system.	NNB
	WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00



SPM STEREO POWER AMPLIFIERS WITH OPTIONAL DSP

SPM Technology (Switching Power Mosfet) amplifiers. High efficiency. Input gain control on the front panel with locking system. Fully protected (clip, thermal and front panel indicators). Progressive forced ventilation, temperature controlled. Built-in anticlip and subsonic filter. Suitable for DSP AMIC and AMIC Lab. Balanced inputs on XLR3 connectors. Speak on outputs.

DPA600	Power Unit 275 W/channel into 4 ohms, 180 W/channel into 8 ohms, 410 W/channel into 2 ohms, 12.4 Kg. 2 u	€ 817,00
DPA1000	Power Unit 440 W/channel into 4 ohms, 275 W/channel into 8 ohms, 682 W/channel into 2 ohms, 15.4 Kg. 2 u	€ 991,00
DPA1400	Power Unit 635 W/channel into 4 ohms, 395 W/channel into 8 ohms, 990 W/channel into 2 ohms, 18.3 Kg. 2 u	€ 1.264,00
DPA2000	Power Unit 940 W/channel into 4 ohms, 550 W/channel into 8 ohms, 1.420 W/channel into 2 ohms, 21,5 Kg. 2 u	€ 1.642,00
DPA4000T	Power Unit 1.880 W/channel into 4 ohms, 1.110 W/channel into 8 ohms, 2.800 W/channel into 2 ohms 33.7 kg. 3 u. Twin power supply	€ 3.165,00
AMIC	DSP card including AMIC Lab software. 4 outputs. Level, mute and remote control adjust. Phase inverter. Delay. Crossover type and slope adjustable. 10 parametric equalizers per channel. Test signal generator. Password locking option. Graphical screen.	€ 411,00
NEW (April 2015) ALMACARD	DSP card including the same processing power as the ALMA24 stand-alone processor. Compatible with the DPA-T series amplifiers. 2 inputs and 4 outputs (2 internal, for the DPA amplifier, and 2 for an external stack amplifier).	€ 411,00
WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Eccler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00



NETWORKABLE STEREO POWER AMPLIFIERS

Networkable amplifiers. Integrated DSP and Ethernet remote control & monitoring. High efficiency SPM TECHNOLOGY (Switching Power Mosfet). Front panel LCD display and local controls. Progressive forced ventilation, temperature driven. Built-in anticlip and subsonic filters. Soft start. XLR inputs and Speakon outputs. 3 rack units

NPA4000T	2 x 1910 W RMS @ 4 ohms. Available upon request (delivery term: 75 days)	€ 3.645,00
WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00

NETWORKABLE MULTICHANNEL POWER AMPLIFIERS

NXA series Powered Digital Audio Manager. Digital matrix, Networkable Zoning Amplifier, with integrated AMIC DSP and remote EclerNet management. 4/6 analogue inputs routable to any output. 4/6 volume remote control ports, assignable to one or various channels. High end A/D and D/A codecs. Assignable and enable/disable function on front knobs. Independent channel working modes: SINGLE mode, BRIDGE and PARALLEL. Class D amplifiers (eco friendly). Silent cooling through convection, without fan (all models). Integrated anti-clip system. RJ45 (Ethernet) remote control port. RS-232 control interface. Auto-Stand By function. Self-test mode function with fault relay. Euroblock type input, output and volume remote control connections. 2RU height.

NXA480	4 x 85 W RMS @ 4 ohms	€ 1.075,00
NXA680	6 x 84 W RMS @ 4 ohms	€ 1.284,00
NXA4200	4 x 202 W RMS @ 4 ohms	€ 1.432,00
NXA6200	6 x 218 W RMS @ 4 ohms	€ 1.797,00
NXA4400	4 x 420 W RMS @ 4 ohms	€ 1.986,00
NEW (April 2015) NXA4700	4 x 700 W RMS @ 4 ohms / 4 x 1200 W RMS @ 2 ohms	NNB
WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00



CEILING SPEAKERS FOR BACKGROUND MUSIC APPLICATIONS
IC: In-ceiling speakers

IC5	Two ways ceiling speaker, 5" woofer plus 13 mm. coaxial soft dome tweeter, low and high impedance (4 power tapping selection + 30 W/8ohms), easily paintable. Unit price. Delivery by pairs	€	39,00
IC6	Two ways ceiling speaker, 6,5" woofer plus 1" coaxial soft dome tweeter, low and high impedance (4 power tapping selection + 40 W/8ohms), easily paintable. Unit price. Delivery by pairs. Price per unit	€	48,00
IC8	Two ways ceiling speaker, 8" woofer plus 1" coaxial soft dome tweeter, low and high impedance (4 power tapping selection + 60 W/8ohms), easily paintable. Unit price. Delivery by pairs	€	65,00
ICSB10L	In-ceiling 10" subwoofer unit. 100 W RMS / 8 ohms. Unit price. Delivery by pairs	€	194,00

IC/IW PLUS: High end in-ceiling speakers

NEW	IC6PLUS	2 way speaker. 6" ferrite magnet woofer built in Kevlar-NBR material + 1" adjustable (pan-tilt) tweeter built in "super-silk" ACCW material. 4 mechanical bodies light weight structure which allows for fast, easy installation (spin gesture + lock clip). 75 W RMS. Optional back can and 100 V line transformer	€	134,00
NEW	IC6PLUSBCAN	Back can for IC6PLUS	€	26,00
	IC6PLUSSTR	100 V line transformer adapter for the IC6PLUS ceiling loudspeaker	€	44,00
NEW	IC8PLUS	2 way speaker. 8" ferrite magnet woofer built in Kevlar-NBR material + 1" adjustable (pan-tilt) tweeter built in "super-silk" ACCW material. 4 mechanical bodies light weight structure which allows for fast, easy installation (spin gesture + lock clip). 100 W RMS. Optional back can and 100 V line transformer	€	169,00
NEW	I 8PLUSBCAN	Back can for IC8PLUS	€	34,00
	IC8PLUSSTR	100 V line transformer adapter for the IC8PLUS ceiling loudspeaker	€	54,00
	IW6PLUS	Two ways in-wall speaker. 6,5" woofer plus coaxial 25 mm tweeter. 40 W RMS / 16 ohms. Frame pre mounting. Speaker assembly and grill can be painted separately and then easily fitted in the frame. Unit price. Delivery by pairs	€	110,00

ECL: PUBLIC ADDRESS CEILING SPEAKERS

ECL106FR	Fire rated ECL106i to obey BS 5839-8, ceramic conector, thermal fuse, fireproof backcan	€	64,00
-----------------	---	---	--------------



SPEAKER CABINETS FOR BACKGROUND MUSIC APPLICATIONS
AMBIT SERIES

	AMB103WH	2 ways plastic injection speaker cabinet. 25 W RMS / 8 ohms. 100 V mode power selector (15, 7.5, 5, 2.5 W). 3,5 " woofer. Bracket included. IP 54. Anti UV treatment. Dimensions (w x h x d) 122 x 122 x 117 mm. Weight 1,165 Kg. Unit price. Delivery by pairs. White color	€	55,00
NEW (April 2015)	AMB103BK	2 ways plastic injection speaker cabinet. 25 W RMS / 8 ohms. 100 V mode power selector (15, 7.5, 5, 2.5 W). 3,5 " woofer. Bracket included. IP 54. Anti UV treatment. Dimensions (w x h x d) 122 x 122 x 117 mm. Weight 1,165 Kg. Unit price. Delivery by pairs. Black color	€	55,00
	AMB106WH	2 ways plastic injection speaker cabinet 50 W RMS / 8 ohms. 100 V mode power selector (30, 15, 7.5, 5 W). 6,5 " woofer. Bracket included. IP 54. Anti UV treatment. Dimensions (w x h x d) 210 x 210 x 160 mm. Weight 2,75 Kg. Unit price. Delivery by pairs. White color	€	88,00
	AMB106BK	2 ways plastic injection speaker cabinet 50 W RMS / 8 ohms. 100 V mode power selector (30, 15, 7.5, 5 W). 6,5 " woofer. Bracket included. IP 54. Anti UV treatment. Dimensions (w x h x d) 210 x 210 x 160 mm. Weight 2,75 Kg. Unit price. Delivery by pairs. Black color	€	88,00
	MP106AMB2WH	Mechanical hardware to link 2 AMBIT 106. White color	€	21,00
	MP106AMB2BK	Mechanical hardware to link 2 AMBIT 106. Black color	€	21,00
	MP106AMB3WH	Mechanical hardware to link 3 AMBIT 106. White color	€	46,00
	MP106AMB3BK	Mechanical hardware to link 3 AMBIT 106. Black color	€	46,00
	MP106AMB4WH	Mechanical hardware to link 4 AMBIT 106. White color	€	69,00
	MP106AMB4BK	Mechanical hardware to link 4 AMBIT 106. Black color	€	69,00
	SR6WH	Wall bracket to complement MP106AMB2 or to be installed for one AMBIT 106 or one AMBIT 108. It allows to install it on the wall or the ceiling. White color	€	57,00
	SR6BK	Wall bracket to complement MP106AMB2 or to be installed for one AMBIT 106 or one AMBIT 108. It allows to install it on the wall or the ceiling. Black color	€	57,00



	AUDEO SERIES		
	AUDEO103WH	Designed by Giugiaro. 2 ways, full range ABS speaker cabinet. IP 54. 3,5" woofer and 13 mm soft dome tweeter. 25 W RMS / 8 Ω. 100 V line power taps: 15/7.5/5/2.5 W. Wall bracket included. 2 units packing. Unit price. Delivery by pairs. White color	€ 79,00
	AUDEO103BK	Designed by Giugiaro. 2 ways, full range ABS speaker cabinet. IP 54. 3,5" woofer and 13 mm soft dome tweeter. 25 W RMS / 8 Ω. 100 V line power taps: 15/7.5/5/2.5 W. Wall bracket included. 2 units packing. Unit price. Delivery by pairs. Black color	€ 79,00
	AUDEO106WH	Designed by Giugiaro. 2 ways, full range ABS speaker cabinet. IP 54. 6,5" woofer and 25 mm soft dome tweeter. 50 W RMS / 8 Ω. 100 V line power taps: 30/15/10/7 W. Wall bracket included. 2 units packing. Unit price. Delivery by pairs. White color	€ 129,00
	AUDEO106BK	Designed by Giugiaro. 2 ways, full range ABS speaker cabinet. IP 54. 6,5" woofer and 25 mm soft dome tweeter. 50 W RMS / 8 Ω. 100 V line power taps: 30/15/10/7 W. Wall bracket included. 2 units packing. Unit price. Delivery by pairs. Black color	€ 129,00
	AUDEO108WH	Designed by Giugiaro. 2 ways, full range ABS speaker cabinet. IP 54. 8" woofer and 25 mm soft dome tweeter. 100 W RMS / 8 Ω. 100 V line power taps: 60/30/15/7.5 W. Wall bracket included. 2 units packing. Unit price. Delivery by pairs. White color	€ 248,00
	AUDEO108BK	Designed by Giugiaro. 2 ways, full range ABS speaker cabinet. IP 54. 8" woofer and 25 mm soft dome tweeter. 100 W RMS / 8 Ω. 100 V line power taps: 60/30/15/7.5 W. Wall bracket included. 2 units packing. Unit price. Delivery by pairs. Black color	€ 248,00
	AUDEO106PWH	Kit of powered AUDEO 106 (master) plus passive (slave) including 3 m. speaker cable. Powered speaker includes a 2x20 W RMS power module to feed master and slave units. AUTOSTANDBY function to save energy. Only low impedance functionality. Designed by Giugiaro. Wall brackets included. White color	€ 233,00
	AUDEO106PBK	Kit of powered AUDEO 106 (master) plus passive (slave) including 3 m. speaker cable. Powered speaker includes a 2x20 W RMS power module to feed master and slave units. AUTOSTANDBY function to save energy. Only low impedance functionality. Designed by Giugiaro. Wall brackets included. Black color	€ 233,00
NEW (March 2015)	AUDEOSB110	10" passive subwoofer, 150 W	NNB
	AUDEOSB110P	10" self-powered subwoofer, 150 W	€ 368,00
NEW (May 2015)	AUDSB110P21	10" self-powered subwoofer + stereo powered satellite output. 150 W Subwoofer way. 2 x 60 W @ 4 Ω / 2 x 120 W @ 2 Ω satellite stereo output. REMOTE port (0-10 VDC) for volume control. MASTER VOL and SUB LEVEL control. Subwoofer way polarity switch. Adjustable subwoofer LPF.	NNB
	DSTANDAUDEO	Display stand top of the table for AUDEO 103 and AUDEO 106 (pair)	€ 44,00
	MSTANDAUDEO	AUDEO speakers adapter for mounting on standard microphone stands	€ 26,00



NEST SERIES

NEST106WH	2 ways, 1/8th sphere shaped installation speaker cabinet. Perfect assembly in corners. 6,5" woofer and $\pm 15^\circ$ adjustable, concentric tweeter. 50 W RMS / 8 ohms. 100 V line transformer with 30 / 15 / 10 and 7 W taps. Only available in white. Unit price. Delivery by pairs. Only available in white color	€	138,00
MP106NEST4	Bracket to fix 4 NEST 106 attached to the ceiling	€	80,00
MP106NEST3	Bracket to fix 3 NEST 106 attached to the wall	€	54,00
MP106NEST2	Bracket to fix 2 NEST 106 attached to the wall	€	44,00

PLASTIC INJECTION SPEAKER CABINETS MOBILE APPLICATIONS
VERSO SERIES

Two ways, full range, high density plastic speaker cabinets. Suitable for fixed, mobile or stage monitor applications. Smart and balanced look, by Giugiaro Design.

VERSO8	150 W RMS / 8 ohms (300 W program). 8" woofer and 25 mm compression driver. Dimensions: 291 x 241 x 398 mm. Weight: 7.1 Kg.	€	243,00
VERSO10	250 W RMS / 8 ohms (500 W program). 10" woofer and 34 mm compression driver. Dimensions: 350 x 290 x 475 mm. Weight: 12.25 Kg.	€	337,00
VERSO12	350 W RMS / 8 ohms (700 W programa). 12" woofer and 44 mm compression driver. Dimensiones: 447 x 368 x 607 mm. Weight: 19.8 Kg.	€	521,00
VERSO8P	Self powered speaker cabinet. 200 W RMS. 8" woofer and 25 mm compression driver. Independent amplifier for Low and High ways. Two MIC/LINE inputs with mixer. Tone controls. Dimensions: 291 x 241 x 398 mm. Weight: 9.8 Kg.	€	396,00
VERSO10P	Self powered speaker cabinet. 300 W RMS. 10" woofer and 34 mm compression driver. Independent amplifier for Low and High ways. Two MIC/LINE inputs with mixer. Tone controls. Dimensions: 350 x 290 x 475 mm. Weight: 15.6 Kg.	€	582,00
VERSO12P	Self powered speaker cabinet. 400 W RMS. 12" woofer and 44 mm compression driver. Independent amplifier for Low and High ways. Two MIC/LINE inputs with mixer. Tone controls. Dimensions: 447 x 368 x 607 mm. Weight: 23 Kg.	€	700,00
VERSOSB115P	15" self-powered subwoofer, 500 W RMS, selectable 100 or 150 Hz LPF, top hat 35 mm, phase and volume controls, opcional wheel-kit (QRA+WH200 kit)	€	991,00
BAGVERSO8	Bag for VERSO 8 / 8P. Ready for transportation and to be used with the speaker in operation.	€	54,00
BAGVERSO10	Bag for VERSO 10 / 10P. Ready for transportation and to be used with the speaker in operation.	€	69,00
BAGVERSO12	Bag for VERSO 12 / 12P. Ready for transportation and to be used with the speaker in operation.	€	100,00
SR8	Wall bracket for VERSO 8, 8P, 10 and 10P	€	57,00
SR12	Wall bracket for VERSO 10, 10P, 12 and 12P	€	77,00



HORNS, PROJECTORS AND OUTDOOR SPEAKERS

PRS10T	ABS weather proof sound projector. IP 55. Power tapings (100 V): 10, 5, 2.5 W RMS. 91 dB SPL 1w/1m. White. 1,6 Kg. Dimensions (diameter x depth): 136x220 mm.	€	103,00
PHS20T	ABS weather proof horn loudspeaker. IP 56. Power tapings (100 / 70 V): 15, 7.5, 3.75, 2 W RMS. 102 dB SPL 1w/1m. White. 1,3 Kg. Dimensions (diameter x depth): 200x233 mm.	€	103,00
MSP50T	ABS weather proof horn loudspeaker. IP 56. Power tapings (100 V): 50, 25, 12.5, 9, 4.5, 3.5 W RMS. 99 dB SPL 1w/1m. Grey. 3,9 Kg. Dimensions : 250x360x320 mm.	€	353,00
IG108	IP65 outdoor speaker, mushroom shape, 100 W at 8 ohms, 100V power taps (7,5, 15, 30 and 60 W), Efficiency (1W/1m) 91 dB SPL, security ground bracket included	€	346,00

PLYWOOD SPEAKER CABINETS FOR INSTALLATION
DACORD: ARCHITECTURAL SERIES

DACOT108IWH	Two ways speaker cabinet (8" woofer + 1" tweeter), Max. RMS power 125 W/8 ohms, embedded nuts flying points, back-hidden handle for easy installation and transport, bracket SR100 available and not included, white color.	€	391,00
DACOT108IBK	Two ways speaker cabinet (8" woofer + 1" tweeter), Max. RMS power 125 W/8 ohms, embedded nuts flying points, back-hidden handle for easy installation and transport, bracket SR100 available and not included, black color	€	391,00
DACOH206IWH	Two ways speaker cabinet (2x6,5" woofer + square horn), Max. RMS power 220 W/8 ohms, embedded nuts flying points, back-hidden handle for easy installation and transport, for vertical or horizontal installation, u-shapped bracket included, white color	€	608,00
DACOH206IBK	Two ways speaker cabinet (2x6,5" woofer + square horn), Max. RMS power 220 W/8 ohms, embedded nuts flying points, back-hidden handle for easy installation and transport, for vertical or horizontal installation, u-shapped bracket included, black color	€	608,00
DACOH208IWH	Two ways speaker cabinet (2x8" woofer + square horn), Max. RMS power 280 W/8 ohms, embedded nuts flying points, back-hidden handle for easy installation and transport, for vertical or horizontal installation, u-shapped bracket included, white color	€	792,00
DACOH208IBK	Two ways speaker cabinet (2x8" woofer + square horn), Max. RMS power 280 W/8 ohms, embedded nuts flying points, back-hidden handle for easy installation and transport, for vertical or horizontal installation, u-shapped bracket included, black color	€	792,00
DACOSB208	Double 8" bandpass reinforcement subwoofer. 300 W RMS @ 4 ohms. Top and bottom flying points. Integrated passive crossover filter. Availbale only in black	€	667,00
DACOSB212	Double 12" subwoofer unit. 400 W RMS / 4 ohms. Available only in black	€	1.101,00
SR100	Wall mount bracket meeting the VESA 100, 75 and 50 standards. Compatible with the DACORDT108i loudspeaker cabinet (VESA 100 compatible). Black color	€	34,00
SRDAWH	Ceiling bracket for DACORD series. White color	€	23,00
SRDABK	Ceiling bracket for DACORD series. Black color	€	23,00



UMA: SOUND REINFORCEMENT SERIES

UMA112I	Two ways speaker cabinet (12" woofer + horn), Max. RMS power 350 W/8 ohms, trapezoidal shape, embedded nuts flying points, top hat for pole mounting, presence switch for high freq. adjustment.	€ 820,00
UMA115I	Two ways speaker cabinet (15" woofer + horn), Max. RMS power 450 W/8 ohms, trapezoidal shape, embedded nuts flying points, top hat for pole mounting, presence switch for high freq. adjustment.	€ 970,00
UMASB118I	Subwoofer 18", Max. RMS power 500 W/8ohms, top hat for pole mounting UMA 112 and UMA 115	€ 1.067,00
SR12	Wall bracket for UMA 12. It allows to install it on the wall.	€ 77,00
POLE01	Pole for UMA SB118 and UMA 12 or UMA 15	€ 36,00

CKL: LONG THROW SERIES

CKL110T	Long throw sound system designed for high intelligible speech. Trapezoidal acoustic enclosure for mid and high frequency reproduction. 2 ways: 10" + 2". 350 W RMS / 8 ohms. 112 dB SPL 1 W 1 m. 6 built-in cargo restraint tracks (ISO 9788) to fly the cabinet. Handles. Dimensions (w x h x d) 550 x 550 x 650 mm. Weight 47 Kg	€ 3.204,00
CKLSM115T	Sound reinforcement for CKL 110. Trapezoidal acoustic enclosure for mid and low frequency reproduction. 15" woofer. 600 W RMS / 8 ohms. 105 dB SPL 1 W 1 m. 6 built-in cargo restraint tracks (ISO 9788) to fly the cabinet. Handles. Dimensions (w x h x d) 550 x 550 x 650 mm. Weight 37,2 Kg	€ 1.767,00
DPC118	Subwoofer 18", Max. RMS power 1000 W/8ohms	€ 2.048,00
WH200	4 wheel kit for DPC 118	€ 92,00
ADP	Cargo restraint double stud	€ 21,00
QRA	4 quick release wheel kit for DPC 118	€ 41,00
BAGDPC118	Bag for DPC 118 speaker cabinet	€ 156,00
BAGCKLT	Bag for CKL 110-T or CKL SM115	€ 156,00

AUDIO / VIDEO ACCESORIES

DLA480	Four transformer unit to convert MPA 4-80 amplifier into 70 V or 100 V line output	€ 414,00
DLA680	Six transformer unit to convert MPA 6-80 amplifier into 70 V or 100 V line output	€ 600,00
DLA600	Dual transformer unit to convert any of our MPA amplifiers, XPA 3000 or DPA 600 into 70 V or 100 V line output	€ 491,00
DAC110E	Distribution Unit. 1 input / 10 mono outputs or 1 input / 5 stereo outputs (balanced)	€ 720,00
ATA11R	Telephone adaptor for mixing units. Permits send and receive simultaneously	€ 429,00
PUM3	Minirack junction piece	€ 16,00
PPM1	Minirack extension piece	€ 29,00



MPAGE SERIES: PAGING CONSOLES

MPAGE1	1-zone paging station compatible with any device including a phantom-powered microphone input (pKUB, SAM series, COMPACT series, AMI2-70, MIMO54, MIMO88, etc.). PAGE control output for third-party remote control. Gooseneck microphone included.	€	161,00
MPAGE4	4-zone paging station for the recently upgraded MIMO54, that now allows for real-time paging. 4 zone selection + ALL & PAGE keys. Selectable chime melody and gooseneck microphone	€	258,00
MPAGE16	Digital paging console for MIMO 88, 16 zones, SELECT ALL, CLEAR and PAGING keys, two user-define function keys (ie: for presets)	€	516,00

WP SERIES: WALL PANELS FOR REMOTE CONTROL

WPTOUCH	Touch-sensitive wall panel remote control with LCD transfective display. Digital remote control, compatible with the incoming MIMO88 digital matrix (CAN-BUS). 2 touch-sensitive keys. 1 touch-sensitive jog wheel. 1 IR receiver. 2x16 char. LCD transfective display. Programmable under the incoming MIMO88 control (digital mode). Compatible with the MIMO54 for both volume control and source selection (analogue mode). Compatible with other products with 0-10 VDC ports (MPA, AMIC, AMPACK, etc.) for volume control (using an external power supply). Recessed or top-wall mount with included accessory	€	269,00
WPVOLIR	IR to 0-10 V DC interface + IR remote control set, compatible with MPA, AMPACK, AMIC, NZA, etc.). Volume UP, DOWN & MUTE functions converted from IR pulses to VCA voltages. Wall panel blind plate with IR receiver and IR activity LED (green-orange-red). Same aesthetics than WPVOL and WPVOL-SR. Recessed or top-wall mount with included accessory. REVO-IR Remote control included.	€	141,00
REVOIR	Ecler infrared remote control. VOL UP, VOL DOWN and MUTE keys. Compatible with pKUB, WPTOUCH & WPVOL-IR.	€	26,00
WPPSU	External wall-plug power supply for the WPTOUCH or WPVOL-IR. Required for AMIC, AMIC24, AMPACK25 or 80 and MPA-R devices. Not required for AMPACK2-70, 4-70, NZA or MIMO88, except in installations with very high amount of WPTOUCH or WPVOL-IR panels.	€	46,00



WPM SERIES: WALL PANELS WITH MAGNETIC FRONT PLATE ASSEMBLY

NEW	WPMSCREEN	EclerNet touch-screen wall panel. The WpmSCREEN is a remote control panel compatible with all the EclerNet products, like MIMO88, NXA series and NPA series. It features a 7" touchscreen, RJ45 Ethernet interface and an integrated UCP (User Control Panel) client and server hardware: no computer is required to become a UCP webserver, once one or more WpmSCREEN units are installed in an EclerNet project. Each unit can be configured by means of the UCP control system as a local zone control or as a global installation control, being able to work simultaneously with other WpmSCREEN units and/or also with third-party UCP clients (iOS®, Android®, Windows®, etc.). The WpmSCREEN includes a power supply unit and surface mount installation box. Its is as well compatible with standard recessed boxes and the standard VESA75 mount system.	€ 715,00
	WPM MIXT	2 channel micro-mixer in the standard Wpm wall panel format. Unbalanced stereo LINE input with VOL, BASS and TREBLE controls. Balanced MIC input with Phantom power and talkover function. Requires external PSU (WP-PSU model recommended: up to 20 WpmMIX-T units could be fed with a single WP-PSU)	€ 113,00
	WPMVOL	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (zone volume). RJ45 standard connector. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 64,00
	WPMVOLJ	Same features as WPMVOL + front panel stereo mini-jack connector.	€ 69,00
	WPMVOLSR	Remote wall panel control for one output zone of a MIMO54 / DAM514 unit (source selection and zone volume). RJ45 standard connector. Volume control compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 80,00
	WPMVOLSRJ	Same features as WPMVOL-SR + front panel stereo mini-jack connector.	€ 85,00
	WPMVOLIR	IR to 0-10 V DC interface + IR remote control set. Volume UP, DOWN & MUTE functions converted from IR pulses to VCA voltages. Wall panel blind plate with IR receiver and IR activity LED (green-orange-red). REVO-IR Remote control included. Compatible with all Ecler 0-10V DC REMOTE control ports (MPA-R, AMIC, AMPACK, etc), including the MIMO88 GPI ports. Surface-mount installation box included.	€ 146,00
	WPMC NXLRM	Connection Wall Plate with Male 3 pin XLR connector. Screw-type connector at the back (no solder needed). Surface-mount installation box included.	€ 59,00
	WPMC NXLRF	Connection Wall Plate with Female 3 pin XLR connector. Screw-type connector at the back (no solder needed). Surface-mount installation box included.	€ 59,00
	WPMC NXJRCA	Connection Wall Plate with 1 x stereo minijack and 2 x RCA connectors. Surface-mount installation box included.	€ 59,00
	WPMHAT3	100 / 70 V line attenuator with integrated 24 VDC priority relay. 3 W maximum output power. Surface-mount installation box included.	€ 69,00
	WPMHAT6	100 / 70 V line attenuator with integrated 24 VDC priority relay. 6 W maximum output power. Surface-mount installation box included.	€ 69,00
	WPMHSL4	100 / 70 V line selector (one out of 4 music program lines). Surface-mount installation box included.	€ 69,00

